

OUTDOOROD150-49B

3000nits single-sided floor standing outdoor high-brightness LCD digital signage



Outdoor Waterproof

The IP56 rating provide full protection against dust and water projection. Built in intelligent heating and cooling, together with a smart automatic air circulation system.



Sunlight Readable Image

Adjusts the brightness of the monitor automatically according to the surrounding lighting conditions. This feature considerably reduces power consumption and increases the monitor's lifetime.



Vandal-Resistant Glass

Protection class IK10 vandal-resistant glass for maximum protection of the display from extreme environmental conditions and external shocks



Intelligent Thermal Management

According to the surrounding environment temperature to adjust the internal temperature, to ensure that the equipment in the appropriate temperature range, to extend the service life of the equipment.

FOR MORE INFORMATION

For more information about CNLC, visit our website at www.cnlcdisplay.com. Copyright © cnlcdisplay All rights reserved. All specifications and descriptions are subject to change without notice. Reproduction without permission is prohibited.



Product Parameters



MODEL

| | | |
|-----------------------------------|---------------------------------------|--|
| DISPLAY | LCD Panel Brand and Model | 49"LG |
| | LCD Panel Withstand Temperature Level | -30° +110° |
| | Brightness (w/o glass) | 3000nits |
| | Resolution | 1920*1080 |
| | Contrast Ratio | 1200/1 |
| | Life span (Typ.) | 50,000 hours |
| | Viewing Angle | 178°/178° |
| FUNCTIONAL CHARACTERISTICS | Response Time (Typ.) | 8ms |
| | No Blackening Defects | Up To 110° (230°F) |
| | Polarized Sunglasses Support | Yes |
| | Ambient Light Sensor | Yes |
| MECHANICAL SPECIFICATIONS | Temperature Control | Yes |
| | Lightning And Leakage Protection | Yes |
| | Heat Dissipation | Air circulation system |
| | Border Width | 100mm |
| POWER | Overall Size | 805*1895*150 |
| | Housing Material | Aluminum Alloy |
| | Painting Color | Black/Gray/Silver/Customize |
| | Thickness of Tempered Glass | 6mm |
| | Tempered Glass Transmittance | 84% |
| POWER | Electricity Supply | Internal |
| | Rated Voltage | 200V-240V ~ 50/60Hz |
| | Power Consumption | 350W |
| | Power Adapter and Brand | MeanWell power adapter / Chint leakage |

ENVIRONMENT

| | |
|------------------------|-------------|
| Operating Temperature | -20°+60° |
| IP Rating | IP56 |
| Life Span/Running Time | 7/ 24 hours |

OPTIONAL

| | |
|---|-----------|
| Touch Panel | nanotouch |
| Input interface | HDMI/USB |
| Simultaneous Touch | Ten Point |
| Outdoor Indoor And Waterproof Touch Support | Touch |
| GSM remotely monitoring | Yes |

INTERFACE IN

| | |
|---------------------|----|
| HDMI 2.1 (HDCP 2.3) | *1 |
| USB 3.0 | *1 |
| Micro SD Slot | *1 |
| Audio | *1 |
| RJ-45 | *1 |

SYSTEM MOTHERBOARD

| | |
|------------------|--|
| Operating System | Android 7.1.2 with optional Android 10.0 |
| Processor | Mali-T764 GPU MP4 Quad-Core GPU |
| Clock Speed | 1.5GHZ |
| RAM | DDR4,2GB |
| ROM | Internal 16GB Emme Flash Memory |
| Multimedia | 4K video decoder, 30/60fps |

CERTIFICATIONS


| | |
|----------------|-----|
| CE / FCC /RoHS | Yes |
|----------------|-----|

FOR MORE INFORMATION

For more information about CNLC, visit our website at www.cnlcdisplay.com. Copyright © cnlcdisplay All rights reserved. All specifications and descriptions are subject to change without notice. Reproduction without permission is prohibited.



Dimensional and structural drawings



FOR MORE INFORMATION

For more information about CNLC, visit our website at www.cnlcdisplay.com. Copyright © cnlcdisplay All rights reserved. All specifications and descriptions are subject to change without notice. Reproduction without permission is prohibited.